

JUMP STARTER



Model GP-JSAP*

Technical Specifications

- Output Voltage DC : 11V to 15 V +5 %.
- AC Input voltage : 240 V /50 HZ.
- Starting Current : 750 Amps
- Peak Current : 1500 Amps
- Internal Battery Capacity : 22 Ah Sealed Lead Acid rechargeable battery.
- External DC Charger : 12V 800mA 3-phase. +-10 %
- Cigarette Lighter Chord : 12 V 20 A with Overload Protection
- Air Compressor : 280 PSI with no load current protection.
- Dimension : 338 mm X 22mm X 38mm
- Weight : 9.6 Kg. Approx.

Benefits:

- Handy, Safe and easy operation.
- Emergency Halogen Light flexible & pivoting light to operate in dark.
- Cigarette lighter option for on the way charging.
- Air Compressor for inflating at emergency situations

NEW PRODUCTS

Lithium ion Jump Starter

GP-E21



- Portable & light Weight
- High Efficiency and Easy Functionality
- Suitable for Charging Laptop, Mobile and Other Accessories.

Batteryless Jump Starter

GP-BL 350 A

GP-BL 800 A



- Ultra-capacitor Based German Technology.
- No internal battery required
- Portable and Light weight
- Maintenance Free with Roboust Design.



Sold & Service by :

APPLE ENERGY PVT. LTD.

G-15 & 406, Hilton Centre, Sector - 11,
CBD Belapur, Navi Mumbai - 400614, India.

marketing@appleenergy.in

HELPLINE :

Sales : +91-8080806938 / 48

Service : +91-8080806918 / 28