

SPARK PLUG TESTER & CLEANER

GP-SPTC

Green Power Spark Plug tester and Cleaner are important part of Gasoline engines. Faulty, oily or soot formation on spark plugs lead to various engine related complaints e.g. Engine cranking but not starting, misfiring, knocking, high fuel consumption, max RPM low, poor pick-up etc. In current practice, whenever such issues are reported, technicians use conventional methods such as using polish paper to clean the spark plug.



TECHNICAL SPECIFICATONS

Model **GP-SPTC**

Working Pressure 5kgf/cm² - 12kgf/cm²

Spark Plug used M10, M12, M14 & M18

Input Voltage 220V, AC, 50 Hz

Electronics Vibretor 220V / 12V

12V / 12KV **Ignition Coil**

FEATURES

- Separate plug cleaning chamber consisting of an abrasive system
- Different rubber adopters provided for cleaning plugs of 10 mm, 12 mm, 14 mm and 18 mm sizes
- Twin testing chamber connected to the compressed air system
- Pressure Regulator is provided



APPLE ENERGY PVT. LTD.

406 & 416, Hilton Centre, Sector - 11, CBD Belapur, Navi Mumbai - 400614. INDIA.

Tel.: +91.22.27564032/33 Fax: +91.22.27564032

marketing@appleenergy.in www.appleenergy.in

Helpline:

: +91.8080806938 / 48Service : +91.8080806918/28